








































TIMBER DOUBLE HUNG RANGE: 906 - 1527.

| | | WIDTH | | | | | | | |
|--------|------|---|---|---|---|---|---|---|---|
| | | 605 | 735 | 895 | 1195 | 1453 | 1773 | 2373 | 2651 |
| HEIGHT | 900 |  DH 906 |  DH 907 |  DH 909 |  DH 912 |  DH 915 |  DH 918 |  DH 924 |  DH 927 |
| | 1015 |  DH 1006 |  DH 1007 |  DH 1009 |  DH 1012 |  DH 1015 |  DH 1018 |  DH 1024 |  DH 1027 |
| | 1190 |  DH 1206 |  DH 1207 |  DH 1209 |  DH 1212 |  DH 1215 |  DH 1218 |  DH 1224 |  DH 1227 |
| | 1365 |  DH 1306 |  DH 1307 |  DH 1309 |  DH 1312 |  DH 1315 |  DH 1318 |  DH 1324 |  DH 1327 |
| | 1500 |  DH 1506 |  DH 1507 |  DH 1509 |  DH 1512 |  DH 1515 |  DH 1518 |  DH 1524 |  DH 1527 |



























Double Glazed Double Hung window with Spiral Balances

:: Weather seals are used in all Aspect's products to ensure maximum water and wind resistance.
 :: All windows and doors are Protim treated and can be factory primed upon customer request.



TIMBER DOUBLE HUNG RANGE: 1806 - 2427.

| | | WIDTH | | | | | | | |
|--------|------|---|---|---|---|---|--|---|---|
| | | 605 | 735 | 895 | 1195 | 1453 | 1773 | 2373 | 2651 |
| HEIGHT | 1750 |  DH 1806 |  DH 1807 |  DH 1809 |  DH 1812 |  DH 1815 |  DH 1818 |  DH 1824 |  DH 1827 |
| | 2105 |  DH 2106 |  DH 2107 |  DH 2109 |  DH 2112 |  DH 2115 |  DH 2118 |  DH 2124 |  DH 2127 |
| | 2405 |  DH 2406 |  DH 2407 |  DH 2409 |  DH 2412 |  DH 2415 |  DH 2418 |  DH 2424 |  DH 2427 |

:: All windows are designed to N4, 2300pa Wind velocity and 200pa Water rating.
 :: All windows are AS2047 compliant.

:: There are two different sash profiles available, a modern square look and the original period look, this can be specified when ordering.

:: The operating sash position can be reversed or reconfigured at the time of ordering to suit the customer. Standard hardware used are spiral balances or jamb liners and catches.

:: The glazing options available are quite varied and range from clear, obscured, tinted and double glazed to help you achieve your personal energy requirements.

:: Other options include counter balanced sash lifting systems, boxed mullions and custom horns. Also aluminium or timber flyscreens, round, raked or arched heads, highlights and fixed sashes can be custom built at customer request.

